

(12)

EUROPEAN PATENT APPLICATION

published in accordance with Art. 158(3) EPC

(21) Application number: 87907521.6

(51) Int. Cl.: H 04 Q 9/00

(22) Date of filing: 11.11.87

Data of the international application taken as a basis:

(86) International application number: PCT/JP 87/00873

(87) International publication number: WO 88/03736 (19.05.88 88/11)

(30) Priority: 12.11.86 JP 269400/86

(71) Applicant: SONY CORPORATION,
7-35 Kitashinagawa 6-Chome Shinagawa-ku,
Tokyo 141 (JP)

(43) Date of publication of application: 09.11.88
Bulletin 88/45

(72) Inventor: KURITA, Tohru Sony Corporation, 7-35,
Kitashinagawa 6-chome, Shinagawa-ku Tokyo 141 (JP)



(54) Designated Contracting States: DE FR GB IT

(74) Representative: Cotter, Ivan John et al, D. YOUNG &
CO. 10 Staple Inn, London WC1V 7RD (GB)

DOC

(54) REMOTE COMMANDER.

(57) A remote commander of a remotely controlled apparatus in which the data transmitted from other remote commander (2) is stored in a memory of the remote commander that belongs to the main body, and the thus stored transmitted data is transmitted again. The data transmitted from the other remote commander (2) is stored in a RAM (1) as a user remote control data, and the data transmitted to the remote commander that belongs to the main body is stored in a ROM (3) as an original remote control data. Further provided is a switching means (4) for selecting the original remote control data and the user remote control data, so that the apparatus can be conveniently used.



EP 0 289 625 A1

00289625

DESCRIPTION

TITLE OF THE INVENTION

REMOTE COMMANDER

TECHNICAL FIELD

5 The present invention relates to a remote commander of
a remotely-controlled apparatus and particularly to a remote
commander of a remotely-controlled apparatus in which data
transmitted from other remote commander is stored in a
memory of a remote commander that belongs to a main body and
10 the thus stored transmitted data is transmitted again.

BACKGROUND ART

 When in general a so-called AV system is arranged by
combining a television receiver made by a company S, a video
tape recorder made by other company, for example, company V
15 and an audio equipment made by, for example, company M, the
respective apparatus are independently operated by remote
commanders of the remotely-controlled apparatus that belong
to the respective apparatus, which fact is inconvenient in
use. To remove this disadvantage, Japanese laid-open patent
20 gazette No. 60-254878 proposed such a remote commander that
can store data transmitted from other remote commander and
which can transmit the thus stored transmitted data again.
In Fig. 1, reference numeral 1 designates a
previously-proposed remote commander capable of
25 re-transmitting the thus transmitted data and 2 a remote
commander of a remotely-controlled apparatus that belongs to
the television receiver made by, for example, the company S,
a remote commander of a remotely-controlled apparatus that
belongs to the video tape recorder made by the company V or
30 a remote commander of a remotely-controlled apparatus that

00289625

belongs to the audio equipment made by the company M. In
this remote commander 2, command operations are determined
by a plurality of operation keys 2a, 2b ... as is
well-known. Also, predetermined transmitting data are
5 transmitted by operating the respective operation keys 2a,
2b ... The remote commander 1 is arranged to switch its
memory mode and transmission mode. In the memory mode of
this remote commander 1, as shown in Fig. 1, a transmitting
section of other remote commander 2 is located in
10 correspondence with a receiving section of this remote
commander 1, whereby when the operation key 2a of the
operations keys 2a, 2b ... is corresponded with, for
example, the key 1a of the desired keys 1a, 1b ... and they
are operated together, data transmitted by operating, for
15 example, the operation key 2a of other remote commander 2 is
stored in the remote commander 1 at its memory section
corresponding, for example, to the operation key 1a. In the
transmission mode of this remote commander 1, when the
operation keys 1a, 1b ... are operated, the transmitted data
20 stored in correspondence therewith are transmitted.
Accordingly, in such a remote commander 1, when data
transmitted in correspondence with the respective operating
keys of the remote commander that belongs to the television
receiver made by the company S, data transmitted
25 in correspondence with the respective operating keys of the
remote commander that belongs to the video tape recorder
made by the company V and data transmitted in correspondence
with the respective operating keys of the remote commander
that belongs to the audio equipment made by the company M
30 are stored in response to the respective operation keys 1a,

00289625

1b ..., the above-mentioned AV system can be operated by the single remote commander 1, which fact is convenient.

In such a remote commander 1, however, when the operation key corresponding to the memory section in which data transmitted from other remote commander is not previously stored is operated, the above-mentioned key operation is treated as a transmission error in the remotely-controlled apparatus.

DISCLOSURE OF INVENTION

In view of such an aspect, the present invention is intended to provide the remote commander 1 which can remove the above-mentioned disadvantages and which can be used more conveniently.

The present invention relates to a remote commander in which data transmitted from other remote commander is stored as user remote control data and the thus stored user remote control data can be transmitted again. This remote commander includes a ROM in which original remote control data is stored.

According to the present invention, the above-mentioned remote commander is provided with a change-over switch by which the user remote control data and the original remote control data can be selectively used.

Further, according to the present invention, the switched condition of the above-mentioned change-over switch is displayed.

Furthermore, according to the present invention, when the user remote control data is used, if the operation key corresponding to the memory section in which the data transmitted from other remote commander is not stored is operated, the original remote control data stored in

00289625

response to this key operation is transmitted.

Thus, according to the present invention, since the remote commander includes the ROM in which the original remote control data is stored, when the equipments, which can be controlled by this original remote control data, are used, it is not necessary to store the transmitting data in response to the operation key in advance. Since the user remote control data and the original remote control data can be selectively used, the remote commander of the invention can be applied to a wide variety of equipments.

In addition, when the user remote control data is used, if the operation key in which data transmitted from other remote commander is not correspondingly stored is operated, the stored original remote control data in response to this operation key is transmitted. Thus, at that time, it is not necessary to store in advance data of the equipments which can be controlled by the original remote control data.

Further, when a wrong key is operated inadvertently, this key operation is not treated as the transmission error.

BRIEF DESCRIPTION OF DRAWINGS

Fig. 1 is a construction diagram showing an embodiment of a conventional remote commander, Fig. 2 is a block diagram of an embodiment of a remote commander according to the present invention and Figs. 3, 4, 5 and 6 are representations used to explain the present invention, respectively.

BEST MODE FOR CARRYING OUT THE INVENTION

An embodiment of a remote commander according to the present invention will hereinafter be described with reference to the drawings.

00289625

In the thus arranged remote commander, upon writing, as shown in Fig. 1, other remote commander 2 is located in an opposing relation to the remote commander of this embodiment. Then, the transmitting-writing change-over switch 6 shown in Fig. 3 is switched to the writing position and thereafter, any one of the operation keys 2a, 2b ... of other remote commander 2 for the transmitted data to be written is operated. Also, one operation key 10i of the corresponding operation keys 10a, 10b ... 10Y in this embodiment is operated, whereby it is decided by the microprocessor 5 whether or not the code is read out on the basis of the signals from the frequency discriminating circuit 8 and the code reading circuit 9. If the code is read out, this code is written in the RAM 11 at its address specified by the thus selected operation key 10i. This operation is repeatedly executed at necessary times.

When the remote commander of this embodiment is utilized as a commander, the transmitting-writing change-over switch 6 is connected to the transmitting position. In this case, when the equipments to be remotely-controlled, for example, the television receiver, the video tape recorder, the audio equipments and so on are all made by, for example, the company S and which can be controlled by the original remote control data, the original code - user code change-over switch 4 is connected to the original code position. At that time, as shown in Fig. 5, it is decided whether the operation keys 10a, 10b ... 10y are operated or not. If they are operated, the original remote control data is read out from the ROM 3 at its address corresponding to, for example, the operation key 10i

00289625

operated. Then, this original remote control data is transmitted from the infrared light emission diode 13 to control the predetermined equipment.

When the original code - user code change-over switch 4 is connected to the user code position and the user remote control data previously written in the RAM 11 is transmitted again, the remote commander of the invention is operated as shown in Fig. 6. At that time, it is decided by the microprocessor 5 whether the operation keys 10a, 10b ... 10y

are operated or not. If the operation key 10i, for example, is operated, it is decided whether the user remote control data is written in the RAM 11 at its address corresponding to the operation key 10i. If it is written therein, the

user remote control data written in this RAM at its address corresponding to the operation key 10i is transmitted to control the predetermined equipment. Also, at that time, if the user remote control data is not written in the RAM 11 at its address corresponding to the operation key 10i, the original remote control data is read out from the ROM 3 at its address corresponding to this operation key 10i and this original remote control data is transmitted.

Since the remote commander of this embodiment is constructed as described above, the transmission data corresponding to each operation key of the remote commander of the television receiver made by, for example, the company S, the transmission data corresponding to each operation key of the remote commander of the video tape recorder made by the company V and the transmission data corresponding to each key of the remote commander of the audio equipment made by the company M can be written in response to the

00289625

display panel 14 displays the switched condition of the original code - user code change-over switch 4, the user can recognize the switched condition at a first sight.

Furthermore, when the user remote control data is used, if
5 the operation key relating to the memory section in which the corresponding transmission data of other remote commander 2 is not stored is operated, the previously-stored original remote control data in response to the operation key is transmitted. Thus, even when the wrong key is
10 operated inadvertently, transmission error can be avoided.

The present invention is not limited to the above-mentioned embodiment but it can take various modifications without departing from the gist of the invention.

15 According to the present invention, since the transmission data corresponding to the respective operation keys of the respective remote commanders made by the plurality of makers can be written in response to the respective operation keys 10a, 10b ... 10y and they can be
20 transmitted again, it is convenient that the equipments made by the plurality of makers can be operated by the single remote commander. Further, there is provided the ROM 3 in which particular original remote control data is stored so that when the equipment, which can be controlled by the
25 original remote control data stored in this ROM 3, is used, the transmission data does not have to be written in advance in response to the operation key. Thus, the remote commander of the invention becomes more useful. By switching the original code - user code change-over switch
30 4, it is possible to select the original remote control data

00289625

respective operation keys 10a, 10b ... 10y. Thus, it is convenient that the AV system arranged by combining the equipments made by the plurality of makers can be operated by the single remote commander.

5 In the foregoing, when the original remote control data of the company S is written in the ROM 3, it is not necessary to write transmission data of each operation key of the remote commander that belongs to the television receiver made by the company S. In this case, even when the
10 original code - user code change-over switch 4 is connected to the user code position, the transmission data is not written in the RAM 11 in response to each operation key of the remote commander that belongs to the television receiver so that as shown in Fig. 6, this original remote control data
15 is read out from the ROM 3, thus controlling the operation of this television receiver satisfactorily. In other words, when the equipment, which can be controlled by the original remote control data stored in the ROM 3, is used, the transmission data does not have to be written in advance in
20 response to the key operation. This makes the remote commander of the invention more useful. The original remote control data and the user remote control data can be selectively used by changing the original code - user code change-over switch 4. For example, in addition to one set
25 of the AV system made by, for example, the company S, a television receiver, a video tape recorder, an audio equipment or the like made by a company different from the company S can be remotely-controlled. Thus, it is convenient that the kinds of remotely-controllable
30 equipments are increased. Further, since the liquid crystal

00289625

and the user remote control data, that is, to
remotely-control the television receiver, the video tape
recorder, the audio equipment or the like made by the
different company in addition to one set of the AV system
5 made by the particular company. Thus, it becomes more
useful that the kinds of the remotely-controllable
equipments are increased. Further, since the liquid crystal
display panel 14 displays the switched condition of the
original code - user code change-over switch 4, it is useful
10 that the user can recognize the switched condition at a
first sight. Furthermore, when the user remote control data
is used, even if the operation key relating to the memory
section in which the corresponding transmission data of
other remote commander 2 is not stored is operated, the
15 previously-stored original remote control data in response
to the operation key is transmitted. Thus, even when the
wrong operation key is operated unintentionally, the
transmission error can be avoided.

20

25

30

00289625

CLAIMS

1. In a remote commander in which transmission data of other remote commander is stored as user remote control data and the thus stored user remote control data can be transmitted again, said remote commander being characterized by a ROM in which original remote control data is stored.

2. A remote commander according to claim 1, characterized in that there is provided a change-over switch which selectively employs said user remote control data and said original remote control data.

3. A remote commander according to claim 2, characterized in that a switched condition of said change-over switch is displayed.

4. A remote commander according to claim 2, wherein when said user remote control data is used, even if an operation key relating to the memory section in which corresponding transmission data of said other remote commander is not stored is operated, said original remote control data stored in response to said operation key is transmitted.

(Substituted)

CLAIMS

1. (after being amended) In a remote commander in which
data transmitted from other remote commander are received,
5 said data are stored as user remote control data
corresponding to respective operation keys and the thus
stored predetermined user remote control data can be
transmitted by operating said operation keys, characterized
in that said remote commander comprises a ROM for storing
10 original remote control data and switching means for
selecting and using said user remote control data or said
original remote control data.

2. (after being amended) A remote commander according to
claim 1, characterized by switched condition display means
15 for displaying the switched condition of said switching
means.

3. (after being amended) A remote commander according to
claim 1, characterized in that when said user remote control
data is used, if an operation key, which is not responsive
20 to said user remote control data, is operated, said original
remote control data stored in response to said operation key
is transmitted.

00289625

FIG. 1





FIG. 2



00289625

FIG. 6




FIG. 5





FIG. 4



EXPLANATION ON REFERENCE NUMERALS

Reference numeral 2 represents other remote commander,
3 the ROM, 4 the original code - user code change-over switch,
5 the microprocessor, 6 the transmitting-writing change-over
5 switch, 7 the infrared light receiving element, 8 the
frequency discriminating circuit, 9 the code reading
circuit, 10a, 10b ... 10y the operation keys, respectively,
11 the RAM, 13 the infrared light emission diode and 14 the
liquid crystal display panel.

10

15

20

25

30

INTERNATIONAL SEARCH REPORT

00289625

International Application No

PCT/JP87/00873

I. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all) *

According to International Patent Classification (IPC) or to both National Classification and IPC

Int.Cl⁴ H04Q9/00

II. FIELDS SEARCHED

Minimum Documentation Searched *

Classification System

Classification Symbols

IPC

H04Q9/00, H03J9/00

Documentation Searched other than Minimum Documentation
to the Extent that such Documents are Included in the Fields Searched *Jitsuyo Shinan Koho
Kokai Jitsuyo Shinan Koho1960 - 1986
1971 - 1986III. DOCUMENTS CONSIDERED TO BE RELEVANT ¹⁴

Category *	Citation of Document, ¹⁵ with indication, where appropriate, of the relevant passages ¹⁷	Relevant to Claim No. ¹⁸
Y	JP, A, 60-254898 = US 4623887 * (General Electric Co.) 16 December 1985 (16. 12. 85) Page 4, column 4 (line 8) to page 5, column 1 (line 12) (Family: none)	1-4
Y	JP, A, 61-111089 (Sony Corporaiton) 29 May 1986 (29. 05. 86) Page 2, column 1, lines 1 to 8 "H04Q9/00" (Family: none)	1-4
Y	JP, A, 61-201571 (NEC Corporation) 6 September 1986 (06. 09. 86) Page 2, column 1 (line 4) to column 4 (line 14) (Family: none) "H04N5/00"	1-4

* Special categories of cited documents: ¹⁴"A" document defining the general state of the art which is not
considered to be of particular relevance"E" earlier document but published on or after the international
filing date"L" document which may throw doubts on priority claim(s) or
which is cited to establish the publication date of another
citation or other special reason (as specified)"O" document referring to an oral disclosure, use, exhibition or
other means"P" document published prior to the international filing date but
later than the priority date claimed"T" later document published after the international filing date or
priority date and not in conflict with the application but cited to
understand the principle or theory underlying the invention"X" document of particular relevance: the claimed invention cannot
be considered novel or cannot be considered to involve an
inventive step"Y" document of particular relevance: the claimed invention cannot
be considered to involve an inventive step when the document
is combined with one or more other such documents, such
combination being obvious to a person skilled in the art

"Z" document member of the same patent family

IV. CERTIFICATION

Date of the Actual Completion of the International Search ¹

January 8, 1988 (08. 01. 88)

Date of Mailing of this International Search Report ²

January 25, 1988 (25. 01. 88)

International Searching Authority ³

Japanese Patent Office

Signature of Authorized Officer ²⁰

This Page is inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLORED OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REPERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images
problems checked, please do not report the
problems to the IFW Image Problem Mailbox**